



---

## ALU TAPE

---

**Revision: 24/05/2013****Page 1****Technical Data:**

Base	Aluminium foil with pressure sensitive acrylic adhesive
Water resistance	Very good
Chemical resistance	Not solvent resistant
UV resistance	Very good UV resistance
Working temperature range	-40°C to +120°C

**Product:**

ALU TAPE is self-adhesive aluminium foil on roll, made with a pressure-sensitive acrylic adhesive that is UV and temperature resistant.

**Uses :**

Sealing chimneys, pipes, insulation panels, air ducts, pipe insulation, etc. Airtight taping of insulation panels and aluminium-coated insulation panels.

**Properties :**

- Water resistant
- UV resistant
- Temperature resistant
- Cannot be applied below -5°C

**Pack size**

*Colours:* aluminium foil

*Packaging:* Roll of 3m X 5cm on blister

**Shelf life**

Two years in unopened package when stored in a cool, dry location at temperatures between +5°C and +25°C.

**Application**

Surfaces must be dry, clean and free of grease. Remove protective film and apply without tension. Smooth out with a cloth or roller to eliminate air bubbles. Apply extra firm pressure on corners.

**Safety recommendations**

Observe the usual rules of industrial hygiene. See packaging for more information.

Remark: This Technical Data Sheet does replace all previous documents. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. Soudal preserves the right to alter its products without prior notice.