



SILICONE GREASE

Revision: 24/05/2013**Page 1****Technical Data:**

Base	100% silicone grease
Colour	White (translucent)
Viscosity	Pasty
Density	Approx. 1 g/ml
Water resistance	Very good
Working temperature range	-60°C to +200°C

Product

Lubricant based on 100% silicone grease for lubricating taps and valves.

Uses

Suitable for metal and plastic taps. Also suitable for lubricating hinges, doors, windows, drawers, rails and bearings and for maintaining bicycles, motorbikes, scooters, garden tools, machines, sports equipment and car doors. Prevents (door) seals from freezing.

Properties

- Water resistant
- Temperature resistant
- High chemical resistance
- Water repellent
- Electrically insulating
- Rust and corrosion resistant
- Not water soluble
- Does not attack rubber seals

Pack size

Colour: transparent white

Packaging: 20 g tube on blister

Shelf life

Four years in unopened package in a cool, dry location at temperatures between +5°C and +25°C.

Application

Surfaces must be dry, clean and free of grease. Apply thin layer on surface. For taps, apply to washer or seals as well as the threaded parts of the tap body. Remove any spots with white gas.

Note:

Treated surfaces are not paintable.

Safety recommendations

Observe the usual rules of industrial hygiene. See packaging for more information.

Remark: This Technical Data Sheet does replace all previous documents. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. Soudal preserves the right to alter its products without prior notice.